



EXTREME FLEX MEDIUM PRESSURE

PROPERTIES

INNERCORE SMOOTHBORE PTFE TUBE.
ANTISTATIC LINER AVAILABLE

REINFORCEMENT 304SS HIGH TENSILE BRAID

JACKETS/COVERS INTEGRAL EXTRUDED SILICONE
JACKET WITH POLYESTER
OVERBRAID

APPLICATION MEDIUM PRESSURE
APPLICATIONS REQUIRING
EXTENDED SERVICE LIFE, TIGHT
INSTALLATIONS

Product Description

EXMP series hose designed and developed for the most severe medium pressure applications. the unique proprietary multi-layer constructions results in an extremely flexible, and durable product the industry can rely on.

PART NUMBER	CONDUCTIVE P/N	HOSE SIZE	I.D. NOMINAL	MAX WORKING PRESSURE	MIN. BURST PRESSURE	MIN. BEND RADIUS
			(in.)	(psi)	(psi)	(in.)
EXMP-04	EXMPC-04	1/4	0.187	3000	12000	1.5
EXMP-05	EXMPC-05	5/16	0.250	3000	12000	2
EXMP-06	EXMPC-06	3/8	0.312	2500	10000	2
EXMP-07	EXMPC-07	7/16	0.375	2250	9000	3
EXMP-08	EXMPC-08	1/2	0.405	2000	8000	3
EXMP-10	EXMPC-10	5/8	0.500	1500	6000	3
EXMP-12	EXMPC-12	3/4	0.625	12000	4800	3.5
EXMP-14	EXMPC-14	7/8	0.750	1100	4400	5
EXMP-16	EXMPC-16	1	0.875	1000	4000	6

Temperature Range: -100°F to 500°F intermittent. -76°F to 300°F continuous.



ALL HOSE INC
341 SHAKER ROAD, EAST LONGMEADOW MA01028
413-224-2102 • FAX: 413-224-2105 • SALES@ALLHOSE-INC.COM
ALLHOSE-INC.COM





EXMP
EXTREME FLEX MEDIUM PRESSURE